CITIZENLAB'S

BITUMEN & ASPHALT

Civil Engineering Testing Equipment





Stainless Steel Tank



MARSHALL WATER BATH 60L (Large Capacity)

Standard: ASTM D5581, D6926, D6931, BS 598-107, AASHTO T245

Water Baths for Marshall Specimens

Used to maintain compacted asphalt specimens at constant temperature. The unit fitted with electronic temperature controller with digital display. Constructed with stainless steel inside chamber and exterior case in powder coated steel sheet. Water circulation system is included to ensure that the samples are heated evenly.

Technical Specifications:

Model Number	CL 2008 X / 004
Temperature Range	From Ambient to +80°C
Temperature Accuracy / Resolution	± 0.5°C / 0.1°C
Usage Capacity	56 Litres
Number of Marshall Specimens	4"/100 mm - Approx. 24 pcs
	6"/150 mm - Approx. 12 pcs
Bath Dimension (mm)	650 (L) x 500 (W) x 240 (H)
Dimension (mm)	885 (L) x 500 (W) x 310 (H)
Approx. Weight	30 kg
Power	220 ~ 240 V, 4000 W, 22 A, 1 Ph, 50 / 60 Hz

^{*1} Copy of Manual Instruction

Copyright 2016 CL Citizenlabs Co. Bhd. All Rights Reserved. Revision 3(All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)