

## DIGITAL SOLVENT RECOVERY STILL APPARATUS

### Solvent Recovery

Our new recovery still is coming with cooling circulation tank and it is move able type to located an ideal location. Circulation cooling tank is coming with water circulation water pump. Recovery unit consist of two integral tanks,which are for contaminated solvent and for the correction of clean redistilled solvent.

#### Main Feature :

- Fully stainless steel design ( main unit & circulation cooling unit)
- Come with circulation cooling unit which consist circulation cooling unit
- Overall efficient and compact design
- Digital thermostatic control unit
- Built-in security devices to prevent overheating



### Technical Specifications :

Model Number	CL 2036 X / 004
Recycling Capacity	10 L / H
Temperature Control Range	50 - 200°C
Heating Power	1000 Watt x 2 nos
Product Dimension (mm)	780 (L) x 452 (W) x 1280 (H)
Packing Dimension (mm)	880 (L) x 552 (W) x 1380 (H)
Approx. Product Weight	46 kg
Approx. Packing Weight	50 kg
Power	220 - 240 V, 1 ph, 50 / 60 Hz

### Unit Consist Of :

Model Number	Parts Description	Qty
CL 2036 X / 004 – P 001	Recovery Still Unit c/w Funnel	1unit.
CL 2036 X / 004 – P 002	Moveable circulation cooling tank c/w water circulation pump	1unit.
CL 7048 SS	Stainless Steel Measuring Jug	1no.

\*1 Copy of Manual Instruction



Digital Thermostatic Controller