### CITIZENLAB'S

WWW.CITIZENLABS.NET

## **AGGREGATE & ROCK**

Civil Engineering Testing Equipment



# DIGIMATIC SAND EQUIVALENT SHAKER (TWIN CYLINDER)

Standard: EN 933-8, ASTM D2419, AASHTO T176, NF XP18-598, UNE 83131, UNI 8520-15, CNR N.27

#### **Assessment of Fine**

The digimatic sand equivalent shaker features consist of digimatic timer (can be set at required time) to increase accuracy and ease of operation compared to a spring-type timer. The unit provides adjustable oscillation speed to confirm with both ASTM & EN test procedure, also eliminating variations from on operator to the next. The unit provides a consistent and repeatable oscillation, eliminating variations from one operator to the next.

#### **Technical Specifications:**

Model Number	CL 1001 X / 004D
Speed Of Strokes	175 - 180 strokes / min
Dimension	770 (L) x 350 (W) x 435 (H) mm
Packing Dimension	830 (L) x 490 (W) x 480 (H) mm
Approx. Weight	44 kg
Packing Weight	55 kg
Power	220-240V, 50 / 60 Hz, 0.8 A, 1 ph,128 W

#### Optional Accessories:

Model Number	Parts Description
CL 1000 X / 002	Sand Equivalent Apparatus



**Timer** 



Twin Cylinder



CL 1000 X / 002

Copyright 2016 CL Citizenlabs Co. Bhd. All Rights Reserved. Revision 3(All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)