

NEW  
2023**Unique Feature :**

1. Circulation air flow system.
2. Built-in ventilation point.
3. D.S LCD Screen features;
  - Time setting
  - Alarm alert
  - Real time clock display
  - Periodic setting

**DIGIMATIC DRYING OVEN 140 LITRES & 240 LITRES**

Standard: ASTM C127/C136/D558/D698/D1559, EN 932-5/1097-5, BS 1377/1924

**Drying Sample**

The Digimatic Drying Oven exterior is a general purpose laboratory used such as soil, concrete, asphalt and aggregate. Internal frame made of stainless steel sheet and external casing coated with hard wearing paint & insulated with thick mineral wool. Heat generated by high precision digital controller & temperature range from RT + 10.0°C to 250°C. All capacity come with fan circulation blower. The oven come with glass viewing door surrounding casing is obtained with 50 mm thick fiber glass & steel shelves.

**Technical Specifications :**

Model Number	CL 1017 SS / 002	CL 1017 SS / 003
Capacity	140 Litres	240 Litres
Temp. Variation	RT +10~250°C	
Temp. Fluctuation	±5.0°C	
Ambient Temperature	+5~40°C	
Number of Heaters	2kW x 1 No.	1.5kW x 2 Nos.
Number of Shelves	2 pcs	3 pcs
Load Per Shelve	25kg For Standard Configuration	
Interior Dimension (mm)	550(W) x 450(D) x 580(H)	600(W) x 500(D) x 880(H)
Exterior Dimension (mm)	670(W) x 610(D) x 950(H)	720(W) x 660(D) x 1170(H)
Weight	54 kg	78 kg
Power	220~240 V, 2 kW, 12 A, 1 Ph, 50/60 Hz	220~240 V, 3 kW, 13 A, 1 Ph, 50/60 Hz

\*1 Copy of Manual Instruction

**Optional Accessories :**

Model Number	Parts Description
CL 1017 SS / 002 – P001	140 Litres Shelves (Galvanized Steel)
CL 1017 SS / 003 – P001	240 Litres Shelves (Galvanized Steel)
CL 1017 SS – A001	Adjustable / Movable Trolley Base

