

WWW.CITIZENLABS.NET

## **AGGREGATE & ROCK**

Civil Engineering Testing Equipment



## **MICRO-DEVAL TESTING MACHINE**

Standard: EN 1097-1 / EN 13450

Used to determine the resistance of aggregates to wear by abrasion. The Micro-Deval is supplied complete with separate control panel fitted with a digital automatic revolutions counter. It consists of a motor driven actuator which transmits the rotation directly to the drum cylinders. Complete with conforming soundproof safety cover. The machne essentially comprises as heavy steel frame of 4 cylinders  $\emptyset$  200 x 154mm (L).

#### Features:

- \* Direct precise of the rotation to the drums ensuring strict conformity to Standards
- \* Soundproof safety protection included
- \* Motor will automatically stop after the specified counter (number of revolution) completed

### **Technical Specifications:**

Model Number	CL 1026 X / 001	
Speed Rotation	100 ± 5 min for 14000 ± 10 revolutions	
Revolution	1000 rpm	
Water Tight & Dust Seal	Yes	
Dimension (mm)	400 (H) x 450 (W) x 1325 (L)	
Approx. Weight	205 kg	
Power	220 - 240V, 50/60 Hz, 1kW	

#### **Unit Consists Of:**

Model Number	Parts Description	Qty
CL 1026 X / 001 - P 001	Stainless Steel Drum Cylinders with Ø 200 x 154mm (L) with Wall Thickness is 3mm & Lid Thickness is 8mm (EN 1097-1)	4nos.
CL 1026 X / 001 - P 002	Stainless Steel Spheres Ball Ø10mm +/-0.5mm 20kg/pack	1pack



**Controller Panel** 

# Optional Accessories :

Model Number	Parts Description
CL 1026 X / 001 - A 001	Stainless Steel Cylinder, Ø 200mm x 400mm (L) (EN 13450) *Abrasive Charge (steel spheres) not required



Internal

Copyright 2016 CL Citizenlabs Co. Bhd. All Rights Reserved. Revision 3(All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)