

HUMIDITY CHAMBER 360L (T.C VERSION)

Standard: EN 196-1,EN 12390-2,EN 12390-9

Temperature & Humidity Control

Basic type humidity chamber specialty designed for construction material such as concrete, cement, mortar and etc. for accelerated curing test. Fully stainless steel at inner chamber and external casing, against humidity corrotion, the uni come with portable humifier, heating element and air compressor connected with digimatic control unit for reliable and high accuracy test performance.

Technical Specifications :

Model Number	CL 3030 X / 012
Humidity Control Range	RH95%
Temp. Control Accuracy	20+-0.5°C
Temp. Control Range	15~40°C
Temp. Flatuation	+-1°C
Heating Power	1000W
Cooling Power	180W
Humidity Accuracy	1%
Humification Power	55W
Humification Capacity	400ml/h
Chamber Space(mm)	700W x 560D x 1100H
Dimension (mm)	1200W x 690D x 1680H
Appx. Weight	180kg
Power	220~240V,1Ph,16A, 50/60Hz

Set Consist Of:

Model Number	Parts Description	Qty
CL 3030 X 011 - P 001	Stainless Steel Shelves	5 nos.
CL 3030 X 011 - P 002	Portable Humifier	1 unit

*1 Copy of Manual Instructions



Internal



Controller