

INITIAL SURFACE ABSORPTION APPARATUS

Standard: BS 1881-208 & 1881:5

Surface Water Absorption

To assess the concrete surface absorption characteristics. The rate of flow of water per unit area into a concrete surface when subjected to a constant head of 200 mm is measured.

Technical Specifications :

Model Number	CL 4024 X / 003N
Dimension (mm)	666 (L) x 284 (W) x 637 (H)
Approx. Weight	13 kg

Set Consists Of :

Model Number	Parts Description	Qty
CL 4024 X / 003 – P 001	Reservoir & Rubber Tubing Set	1set
CL 4024 X / 003 – P 002	Scale Board Unit (Stand Rod x2, Board with Scale & Reservoir Holder x1 and Capillary Tube x1)	1set
CL 4024 X / 003 – P 003	Cap Clamp Set (Set of 2 pcs)	1set
CL 4024 X / 003 – P 004	Ø100mm Surface Transparent Acrylic Cap. (Horizontal Type)	1no.
CL 4024 X / 003 – P 005	Carrying Case	1no.
CL 7000 P / 001	Plastic Measuring Cylinder	1no.
CL 7028 P / 001	Plastic Funnel Ø90 mm	1no.

*1 Copy of Manual Instruction

Optional Accessories :

Model Number	Accessories Description
CL 4024 X / 003 – A 001	Transparent Acrylic Cap. (Vertical Type)
CL 4024 X / 003 – A 002	Ø 80mm Surface Transparent Acrylic Cap. (Horizontal Type)
CL 4024 X / 003 – A 003	Soft Clay Pack



CL 4024 X / 003 - A 003



CL 4024 X / 003 - A 001

