

ADVANCE AUTOMATIC DIGITAL CONE PENETROMETER

Standard: BS 1377:2, ASTM D217 and ASTM D937

Liquid Limit : Cone Method

Newly up graded design come with fully automated system for easy operation and high accuracy result. Used to determine the moisture content of clay soil pass from plastic to a liquid status.

FEATURES:-

- *Solid & compact design
- *With find height adjustable system
- *Selectable penetration timer
- *Immediate print result (Optional)

Technical Specifications :

Model Number	CL 5003 X / 005
Accuracy	0.01 mm
Penetration Range	Up to 50 mm
Display Unit	Digimatic Display
Product Dimension (mm)	310 (L) x 210 (W) x 500 (H)
Packing Dimension (mm)	340 (L) x 240 (W) x 470 (H)
Approx. Product Weight	5.5 kg
Approx. Packing Weight	6.5 kg
Power	220 V, 50 / 60 Hz, 1 ph

Unit Consists Of :

Model Number	Parts Description	Qty
CL 5003 X / 005 – P 001	Penetration Test Cone 30° Angle	1no.
CL 5003 X / 002 – P 002	Test Gauge Disk	1no.
CL 5003 X / 005 – P 003	Sample Container Ø 55 x 40 mm	1no.

*1 Copy of Manual Instruction

Optional Accessories :

Model Number	Accessories Description
WH-T1AZBO	Portable Mini Printer (T1)
CL 5003 X / 005 - A 001	Straightedge (100 mm)
CL HWPR - 44	High White Paper Roll 44mm x 33mm Dia. (5rolls/pack)
CL ERC - 05	Seamless Ribbon (Black)



Portable Mini Printer (T1)