

WWW.CITIZENLABS.NET



Drilling Apparatus

Designed to drill small holes in every sector mounts an Emak 2-stroke engine with chrome cylinder and forged-steel drive shaft and connecting rod. The engine controls are grouped together on just one hand making them the ideal solution for single man.

Auger Head **NEED TO ORDER SEPARATELY.**

	O 161 41	
Tachnical	Spacifications	
Technical	Specifications	
		_

·			
Model Number	CL 5013 X / 002		
Drill			
Reduction Ratio	40 : 1		
Punte-bits	Ø10 cm , Ø15 cm, Ø20 cm		
Reduction Gearbox with Grease	Yes		
Engine			
Туре	Air-cooled Two Cycle Engine		
Alternate Code	1E44F-2A		
Power	1.4KW / 6500 r/min		
Idle Speed	3000 ± 200r		
Clutch Speed	4000 ± 300r		
High Speed	8500 ± 300r		
Total Displacement	51.7 CC		
Way of Ignition	Electric Ignition (CDI)		
Ignition System	Transistor Magneto		
Form of Carburettor	Diaphragm		
Fuel Applicable	Gasoline		
Tank Capacity	1.2L		

Set Consists Of:

Model Number	Description	Qty
CL 5013 X / 001 – P001	Set of Operation &Maintenance Tools	1set
CL 5013 X / 001 – A002	100mm Dia. x 800 mm lg. Auger Head	1set
CL 5013 X / 001 – A003	150mm Dia. x 800 mm lg. Auger Head	1set
CL 5013 X / 001 – A004	200mm Dia. x 800 mm lg. Auger Head	1set

Optional Accessories:

Model Number	Description
CL 5013 X / 002 – A001	Extension Rod 300mm lg.



