

VIBRATING COMPACTION HAMMER

Standard: EN 13286-4 (Annex A), BS 1377:4/
BS 1924:2

Vibration Compaction Hammer

The hammer is used for compacting of Proctor and CBR Soil specimen. By changing appropriate tamping foot, it also can be used for compacting concrete cube or beam specimens and compacting asphalt in the percentage refusal density test (PRD Test). **Supplied without accessories** which have to be order separately.

Technical Specifications :


Model Number	CL 5021 X / 001
Alternate Code	DH 0810
Impact Rate	2900 / 3480 min
Dimension (mm)	440 (L) x 95 (W) x 240 (H)
Approx. Weight	6.3 kg
Power	220 V, 1 ph, 50 / 60 Hz, 1050 W

Optional Accessories :

Model Number	Accessories Description	Weight
CL 5021 X / 001 – A 001N	Supporting Frame	63 kg
CL 5021 X / 001 – A 002	Proctor Tamping Foot (Ø 100 mm)	1.2 kg
CL 5021 X / 001 – A 003	Proctor, CBR & PRD Tamping Foot Ø 145 mm	2.3 kg
CL 5021 X / 001 – A 004	100 mm Concrete Cube Tamping Foot 90 x 90 mm	1.7 kg
CL 5021 X / 001 – A 005	150 mm Concrete Cube Tamping Foot 140 x 140 mm	3.5 kg
CL 5021 X / 001 – A 006	Steel Shank 250 mm (L)	0.6 kg



NEW
2018



CL 5021 X / 001 - A004
& A005



CL 5021 X / 001 - A002,
A003 & A006